



■ Tapping Machine Adapters

CORPORATION MODEL / SIZE	OUTLET THREADS*	MUELLER TAPPING MACHINES			HAYS TAPPING MACH. NO. B-1	REED CDTM1000 & 2000;TM1000	RIDGID MLT 3401
		NO. B-100 & B-101	NO. B	NO. A-2 & A-3			
4701-22 5/8 x 3/4 4701T 5/8 x 3/4 4701-22 3/4 4704-22 3/4 4701Q 3/4 4704Q 3/4 4701T 3/4 4704T 3/4 4701B-22 3/4 4704B-22 3/4 4701BQ 3/4 4704BQ 3/4 4701BT 3/4 4704BT 3/4	3/4" Copper	680600	680600	680600	353-06-106	98423	92182
4701-33 3/4 4704-33 3/4 4701-3T 3/4 4704-3T 3/4 4701-44 3/4 4704-44 3/4 4701-55 3/4 4704-55 3/4 4701-22 3/4 x 1 4704-22 3/4 x 1 4701-22 1 4704-22 1 4701Q 1 4704Q 1 4701T 3/4 x 1 4704T 3/4 x 1 4701T 1 4704T 1 4701B-33 3/4 4704B-33 3/4 4701B-3T 3/4 4704B-3T 3/4 4701B-44 3/4 4704B-44 3/4 4701B-55 3/4 4704B-55 3/4 4701B-22 3/4 x 1 4704B-22 3/4 x 1 4701B-22 1 4704B-22 1 4701BQ 1 4704BQ 1 4701BT 3/4 x 1 4704BT 3/4 x 1 4701BT 1 4704BT 1	1" Copper	680601	680601	680601	353-06-108	98424	92187
4701-33 1 4704-33 1 4701-3T 1 4704-3T 1 4701-44 1 4704-44 1 4701-55 1 4704-55 1 4701-22 1 x 1 1/4 4704-22 1 x 1 1/4 4701-22 1 1/4 4704-22 1 1/4 4701Q 1 1/4 4704Q 1 1/4 4701T 1 x 1 1/4 4704T 1 x 1 1/4 4701T 1 1/4 4704T 1 1/4 4701B-33 1 4704B-33 1 4701B-3T 1 4704B-3T 1 4701B-44 1 4704B-44 1 4701B-55 1 4704B-55 1 4701B-22 1 x 1 1/4 4704B-22 1 x 1 1/4 4701BQ 1 x 1 1/4 4704BT 1 x 1 1/4 4701BT 1 x 1 1/4	1 1/4" Copper	680602	--	680602	353-06-110	--	--
4701Q 1 1/2 4704Q 1 1/2 4701BQ 1 1/2 4704BQ 1 1/2	1 1/2" Special	--	--	680421	--	--	--
4701Q 2 4704Q 2 4701BQ 2 4704BQ 2	2" Special	--	--	680422	--	--	--
4701-22 1 1/2 4704-22 1 1/2 4701T 1 1/2 4704T 1 1/2 4701B-22 1 1/2 4704B-22 1 1/2 4701BT 1 1/2 4704BT 1 1/2 4701B-44 1 1/2 4704B-44 1 1/2	1 1/2" Copper	--	--	88640	--	--	--
4701B-33 1 1/2 4704B-33 1 1/2 4701B-22 1 1/2 x 2 4704B-22 1 1/2 x 2 4701BT 1 1/2 x 2 4704BT 1 1/2 x 2 4701-22 2 4704-22 2 4701T 2 4704T 2 4701B-22 2 4704B-22 2 4701BT 2 4704BT 2 4701B-33 2 4704B-33 2 4701B-44 2 4704B-44 2	2" Copper	--	--	88641	--	--	--

■ Maximum Size Drills to be used with A.Y. McDonald Corporation Stops • Per AWWA C-800 Table 1

CORPORATION SIZE	1/2"	5/8"	5/8" x 3/4"	3/4"	3/4" x 1"	1"	1 1/4"	1 1/2"	2"
Corp Stop with AWWA Thread Inlet	7/16"	9/16"	9/16"	11/16"	11/16"	15/16"	1 3/16"	1 7/16"	1 7/8"
Corp Stop with I. P. Thread Inlet	7/16"	--	--	11/16"	11/16"	7/8"	1 1/8"	1 7/16"	1 3/4"

*Threads per AWWA
C-800, Table 4



WARNING: Beginning January 1, 2010, it is unlawful in CALIFORNIA and VERMONT to use any product in the installation or repair of any public water system or any plumbing in a facility or system that provides water for human consumption if the wetted surface area of the product has a weighted average lead content greater than 0.25%. This prohibition does not extend to service saddles used in the state of CALIFORNIA.

A.Y. McDONALD MFG CO.

4800 Chavenelle Road • P.O. Box 508 • Dubuque, IA 52004-0508
563-583-7311 • TOLL FREE 800-292-2737 • FAX 800-832-9296
sales@aymcdonald.com • www.aymcdonald.com

(OVER)

IMPORTANT NOTICE

A.Y. McDonald waterworks products are designed for reliable service. Like all brass products, however, they can be damaged by improper handling and use.

CAUTION:

1. PROTECT THREADS Nicks or distorted threads, especially on tapered threads, can cause leaks.
2. USE A GOOD THREAD SEALANT where threads are intended to provide a leak-proof connection. Do not overtighten.
3. DO NOT use Vaseline®, plumber's grease, or any other petroleum product on seals or o-rings.
4. USE OF A SMOOTH JAWED WRENCH on the flats provided nearest the thread being made up is preferred. Loose fitting pipe wrenches, improperly applied, can distort the body and cause a leak, especially on valves.
5. When installing ball corp valves with tapping machines, follow tapping machine instructions. Valve should be assembled with the machine until it feels solid. Do not attempt to force the valve to its permanent tightness with the machine. **DO NOT OVERTIGHTEN.** Additional tightening required should be done by hand. Reference step 3.
6. AVOID DROPPING or the use of a hammer on any upright plug or key type valve. Impacts, causing dents or distortion, can cause leaks by unseating the plug portion of the valve.
7. BACKFILL CAREFULLY so as to avoid damage to the service line and connections. Looping of the service piping, especially on corporation connections from the main, is recommended to minimize strain on the connections.
8. HIGH PRESSURE INSTALLATION Standard AWWA tapered plug valves are intended for not more than 100 PSIG water in sizes 1/2", 3/4" and 1" and 80 PSIG water for 1-1/4", 1-1/2" and 2" valves. If used for gas service, the maximum Pressure for all-brass plug valves is 25 PSIG.
9. FIELD TESTING Special high pressure field testing may require capping the outlet of corporation stops, curb stops and angle meter stops.
10. PRESSURE TEST for leaks before backfilling.

NOTE: For corps with Kitec® ends, remove Kitec® adaptor prior to drilling. Reassemble Kitec® adaptor to corp after drilling. Inspect all O-rings for damage prior to reassembly.

NOTE: For installations having pressures in excess of 100 PSIG (1/2", 3/4" and 1" corp stops) or 80 PSIG (1-1/4", 1-1/2" and 2" corp stops), the use of McDonald "ball-style" corporation stops is recommended. Ball corporations are for use with water only and are rated at 300 PSIG water pressure.

DAMAGE CAUSED BY IMPROPER USE AND HANDLING WILL VOID OUR WARRANTY.

CORPORATION MODEL / SIZE						■ Drilling Machine Adapters												
						OUTLET THREADS*		MUELLER DRILLING MACHINES		ROMAC TAPMATE TOO	HAYS DRILLING MACHINES		FORD DRILLING MODEL 77	REED DRILLING		RIDGID		
								E-4 & E-5	D-4 & D-5		5930	5935		DM1000 & 2000	DMPVC	RT 1000	RT 3422	MLT 3401
4701-22 5/8 x 3/4	4701B-22 3/4	4704T 3/4	3/4"	52019	37902	351-05-506	354-05-506	355-05-506	DMA2-3	08423	04426	83317	76057	92097				
4701T 5/8 x 3/4	4701BQ 3/4	4704B-22 3/4	Copper															
4701-22 3/4	4701BT 3/4	4704BQ 3/4																
4701Q 3/4	4704-22 3/4	4704BT 3/4	1"	36750	37903	351-05-508	354-05-508	355-05-508	DMA2-4	08424	04427	83322	76067	92012				
4701T 3/4	4704Q 3/4	4704Q 1																
4701-33 3/4	4701B-55 3/4	4704T 3/4 x 1																
4701-3T 3/4	4701B-22 3/4 x 1	4704T 1																
4701-44 3/4	4701B-22 1	4704B-33 3/4																
4701-55 3/4	4701BQ 1	4704B-3T 3/4																
4701-22 3/4 x 1	4701BT 3/4 x 1	4704B-44 3/4																
4701-22 1	4701BT 1	4704B-55 3/4																
4701Q 1	4704-33 3/4	4704B-22 3/4 x 1																
4701T 3/4 x 1	4704-3T 3/4	4704B-22 1																
4701T 1	4704-44 3/4	4704BQ 1																
4701B-33 3/4	4704-55 3/4	4704BT 3/4 x 1																
4701B-3T 3/4	4704-22 3/4 x 1	4704BT 1																
4701B-44 3/4	4704-22 1	4704BT 1																
4701-33 1	4701B-44 1	4704-22 1 1/4	1 1/4"	45385	37904	351-05-510	354-05-510	355-05-510	DMA2-5	--	--	--	76072	92107				
4701-3T 1	4701B-55 1	4704Q 1 1/4																
4701-44 1	4701B-22 1x 1 1/4	4704T 1 x 1 1/4																
4701-55 1	4701BQ 1x 1 1/4	4704T 1 1/4																
4701-22 1 x 1 1/4	4701BT 1 x 1 1/4	4704B-33 1																
4701-22 1 1/4	4704-33 1	4704B-3T 1																
4701Q 1 1/4	4704-3T 1	4704B-44 1																
4701T 1 x 1 1/4	4704-44 1	4704B-55 1																
4701T 1 1/4	4704-55 1	4704B-22 1 x 1 1/4																
4701B-33 1	4704-22 1 x 1 1/4	4704BT 1 x 1 1/4																
4701B-3T 1																		
4701Q 1 1/2	4704Q 1 1/2	4704BQ 1 1/2	1 1/2" Special	501949	507644	351-05-712	--	--	DMA4-6-Q	--	--	--	84007	92157				
4701BQ 1 1/2			Special	508199	507645	351-05-716	--	--	DMA4-7-Q	--	--	--	84012	92162				
4701Q 2	4704Q 2	4704BQ 2	1 1/2" Copper	501947	37905	351-05-512	--	355-05-512	DMA2-6	08425	--	--	76077	92112				
4701BQ 2																		
4701-22 1 1/2	4701B-44 1 1/2	4704B-22 1 1/2																
4701T 1 1/2	4704-22 1 1/2	4704BT 1 1/2																
4701B-22 1 1/2	4704T 1 1/2	4704B-44 1 1/2	2"	508201	37906	351-06-516	--	355-37	DMA2-7	08426	--	--	76082	92117				
4701BT 1 1/2																		
4701B-33 1 1/2	4701BT 2	4704-22 2																
4701B-22 1 1/2 x 2	4701B-33 2	4704T 2																
4701BT 1 1/2 x 2	4701B-44 2	4704B-22 2																
4701-22 2	4704B-33 1 1/2	4704BT 2																
4701T 2	4704B-22 1 1/2 x 2	4704B-33 2																
4701B-22 2	4704BT 1 1/2 x 2	4704B-44 2																