



# SWIVELS, NUTS & GASKETS


## A.Y. McDONALD GAS DISTRIBUTION PRODUCTS

### SWIVELS - NON INSULATED

	DESCRIPTION	BLACK	GALVANIZED	LENGTH	THREAD SIZE
<b>5LT</b>	5LT Straight	4815-726	4815-728	2 1/8"	1/2" NPT
	5LT 3/8" Offset	4815-667	4815-669	2 1/8"	1/2" NPT
	5LT 1 1/4" Offset	4815-822	4815-824	3"	1/2" NPT
<b>10LT</b>	10LT Straight	4815-503	4815-519	2 5/16"	3/4" NPT
	10LT 1/2" Offset	4815-802	4815-804	2 5/16"	3/4" NPT
	10LT 1" Offset	4815-505	4815-521	3 1/8"	3/4" NPT
	10-5LT 1 3/4" Offset	4815-704	4815-706	3"	1/2" NPT
	10LT 1 1/4" Offset	4815-675	4815-677	3 1/4"	3/4" NPT
	10LT 3 15/16" Offset	4815-818	4815-820	4 1/8"	3/4" NPT
	10-5LT 3" Offset	4815-679	4815-681	4"	1/2" NPT
	10LT Elbow	4815-738	4815-740	N/A	3/4" NPT
<b>1A</b>	1 A Straight	4815-537	4815-551	2 1/8"	3/4" NPT
	1 A Straight	4815-539	4815-553	2 13/32"	1" NPT
	1 A 1" Offset	4815-515	4815-531	2 11/16"	3/4" NPT
	1 A Spud	4815-535	4815-549	1 1/8"	3/4" FIP
<b>20LT</b>	20LT Straight	4815-509	4815-525	2 3/4"	1" NPT
	20LT Straight	4815-863	4815-864	4"	1" NPT
	20LT 1" Offset	4815-511	4815-527	3 1/2"	1" NPT
	20LT 1 1/4" Offset	4815-584	4815-586	3 25/32"	1" NPT
	20-10LT 1 5/8" Offset	4815-683	4815-685	3 3/4"	3/4" NPT
	20-5LT 3" Offset	4815-541	4815-555	3 1/2"	1/2" NPT
	20-10LT 3 5/8" Offset	4815-712	4815-714	3 1/2"	3/4" NPT
	20-10LT Straight	4815-730	4815-732	2 3/8"	3/4" NPT
	20-10LT Elbow	4815-814	4815-816		3/4" NPT
	20LT Elbow	4815-691	4815-693	2 1/16" X 2 7/32"	1" NPT
<b>30LT</b>	30LT Straight	4815-545	4815-559	2 29/32"	1 1/4" NPT
	30LT Straight	4815-867	4815-868	2 1/2"	1 1/4" NPT
	30LT 1" Offset	4815-547	4815-561	3 3/4"	1 1/4" NPT
	30LT 1 1/2" Offset	4815-871	4815-872	3 3/4"	1 1/4" NPT
	30-20 Straight	4815-687	4815-689	2 27/32"	1" NPT
	30-20 1 1/4" Offset	4815-616	4815-618	3 25/32"	1" NPT
	30-10LT 3" Offset	4815-840	4815-842	4"	3/4" NPT
	30LT Elbow	4815-875	4815-876		1 1/4" NPT
<b>45LT</b>	45LT Straight	4815-568	4815-578	2 15/16"	1 1/2" NPT
	45LT 1" Offset	4815-570	4815-580	4"	1 1/2" NPT
	45LT 2 1/2" Offset	4815-572	4815-582	5 1/2"	1 1/2" NPT
	45-30LT Straight	4815-734	4815-736	3 7/8"	1 1/4" NPT
	45-30LT 1 5/8" Offset	4815-852	4815-854	4"	1 1/4" NPT
<b>#2</b>	#2 Straight	4815-844	4815-846	3 1/8"	1 1/4" NPT
<b>#3/#4</b>	#3 Straight	4815-620	4815-622	2 14/16"	1 1/2" NPT
	#3/#4 Straight	4815-856	4815-857	3 1/8"	1 1/2" NPT
<b>60 LT</b>	60LT Straight	4815-826	4815-828	2 7/8"	1 1/2" NPT
	60LT 1 1/2" Offset	4815-879	4815-880	5 3/8"	1 1/2" NPT
<b>5A</b>	5A Straight	4815-810	4815-812	2 1/8"	2" FNPT
<b>100 LT</b>	100LT Straight	4815-696	4815-698	3 3/4"	2" NPT

SEE NEXT PAGE FOR INSULATED STYLES

ADDITIONAL PRODUCTS ON REVERSE SIDE



## SWIVELS - INSULATED


	DESCRIPTION	ZINC PLATED	LENGTH	THREAD SIZE
<b>1A</b>	1A Spud	4815-723	1"	3/4" FNPT
	1A Straight	4815-755	2 3/8"	3/4" NPT
	1A Straight	4815-760	2 3/8"	1" NPT
	1A 1" offset	4815-765	2 3/4"	3/4" NPT
<b>20LT</b>	20LT Straight	4815-746	2 3/4"	1" NPT
	20LT 1 1/4" Offset	4815-748	3 11/16"	1" NPT
	20-10LT Straight	4815-773	2 3/8"	3/4" NPT
	20-10LT Spud	4815-779	1 1/4"	3/4" NPT
<b>30LT</b>	30LT Straight	4815-796	3"	1 1/4" NPT
	30LT 1" Offset	4815-791	3 1/2"	1 1/4" NPT
	30-20LT Straight	4815-786	2 7/8"	1" NPT

All insulated swivels are zinc plated for corrosion protection. The zinc is applied after machining so the threads are also protected.

**MANY MORE INSULATED SIZES ARE COMING SOON!**



**NUTS**



**GASKETS**



**PLUGS**

SIZE	BLACK	GALVANIZED		BLACK
5LT	4815-671	4815-673	4820-197	4815-836
10LT	4815-501	4815-517	4820-184	4820-181
1A	4815-513	4815-529	4820-185	4820-180
OEMCO	4815-564	4815-574	4820-185	
20LT	4815-507	4815-523	4820-186	4820-182
30LT	4815-543	4815-557	4820-187	4815-663
45LT	4815-566	4815-576	4820-188	4815-665
#2	4815-848	4815-850	4820-193	
#3/#4	4815-624	4815-626	4820-190	
60LT	4815-830	4815-832	4820-192	
5A	4815-806	4815-808	4820-191	
100LT	4815-700	4815-702		

\*Plugs can be tapped 1/8" or 1/4". Contact Factory.

## METER ADAPTERS



The McDonald meter adapters are used to efficiently convert from one meter size to another. Each adapter comes with a flat gasket seal on the female end. In addition, each fitting is zinc plated for corrosion protection. The zinc is applied after machining so the threads are also protected.

If you are converting meter sizes in your system, consider these fittings for a cost effective approach.

Manufactured per ANSI B109.1

Part #	Male Meter Thread (converting from)	Female Meter Thread (converting to)
4820-006	1A	20LT
4820-007	10LT	20LT
4820-008	1A	10LT


**SEE OUR FULL CATALOG FOR 3-PART INSULATED UNIONS**

1/09



**A. Y. McDonald Mfg. Co.**

GAS VALVES | WATERWORKS | PLUMBING VALVES | PUMPS



800.292.2737 | FAX 800.832.9296 | sales@aymcdonald.com | www.aymcdonald.com