




Copper Tube Slip Joint Compression Connector



The McDonald Slip Joint Compression Coupling is a simple, convenient method for connecting to copper tube.

The steps listed below will make your job easier and assure fast, safe, and watertight connections:

1. Tighten the Slip Joint nut to:


1" size.....35 ft-lbs.

This compresses the gasket for watertight connections. Overtorquing nut by 10-20 ft-lbs. will not affect connections.

2. Use only on cold water Services.



Copper Tube Slip Joint Compression Connector



The McDonald Slip Joint Compression Coupling is a simple, convenient method for connecting to copper tube.

The steps listed below will make your job easier and assure fast, safe, and watertight connections:

1. Tighten the Slip Joint nut to:


1" size.....35 ft-lbs.

This compresses the gasket for watertight connections. Overtorquing nut by 10-20 ft-lbs. will not affect connections.

2. Use only on cold water Services.



Copper Tube Slip Joint Compression Connector



The McDonald Slip Joint Compression Coupling is a simple, convenient method for connecting to copper tube.

The steps listed below will make your job easier and assure fast, safe, and watertight connections:

1. Tighten the Slip Joint nut to:


1" size.....35 ft-lbs.

This compresses the gasket for watertight connections. Overtorquing nut by 10-20 ft-lbs. will not affect connections.

2. Use only on cold water Services.



Copper Tube Slip Joint Compression Connector



The McDonald Slip Joint Compression Coupling is a simple, convenient method for connecting to copper tube.

The steps listed below will make your job easier and assure fast, safe, and watertight connections:

1. Tighten the Slip Joint nut to:

1" size.....35 ft-lbs.

This compresses the gasket for watertight connections. Overtorquing nut by 10-20 ft-lbs. will not affect connections.

2. Use only on cold water Services.



IMPORTANT NOTICE - READ CAREFULLY

Installation Instructions

Copper Tube Slip Joint Compression Connector

A.Y. McDonald waterworks products are designed for reliable service. Like all brass products, however, they can be damaged by improper handling and use.

CAUTIONS

1. Protect threads. Avoid loose fitting wrenches. Do not drop or impact.
2. Use extra care with high water pressures (over 100 PSIG) and pipe over 1". Consult factory if desired.
3. Inspect and test all joints, valves and fittings before backfilling.
4. Backfill carefully so as to avoid damage to the service line and connections. Looping of the service lines is recommended to minimize strain.
5. DO NOT use Vaseline®, plumber's grease, or any other petroleum based product on seals or o-rings.

Damage caused by improper use and/or handling will void our warranty

WARNING: It is unlawful in CALIFORNIA & VERMONT (effective 1/1/2010); MARYLAND (effective 1/1/2012); LOUISIANA (effective 1/1/2013) and the UNITED STATES OF AMERICA (effective 1/4/2014) to use any product in the installation or repair of any public water system or any plumbing in a facility or system that provides water for human consumption if the wetted surface area of the product has a weighted average lead content greater than 0.25%. This prohibition does not extend to service saddles used in California, Louisiana or under USA Public Law 111-380. **WARNING:** This product can expose you to chemicals including lead, which is known to the State of CALIFORNIA to cause cancer and birth defects or other reproductive harm. For more information go to: www.P65Warnings.ca.gov.

3210-666

(OVER)

800.292.2737 | sales@aymcdonald.com | aymcdonald.com

4/22



IMPORTANT NOTICE - READ CAREFULLY

Installation Instructions

Copper Tube Slip Joint Compression Connector

A.Y. McDonald waterworks products are designed for reliable service. Like all brass products, however, they can be damaged by improper handling and use.

CAUTIONS

1. Protect threads. Avoid loose fitting wrenches. Do not drop or impact.
2. Use extra care with high water pressures (over 100 PSIG) and pipe over 1". Consult factory if desired.
3. Inspect and test all joints, valves and fittings before backfilling.
4. Backfill carefully so as to avoid damage to the service line and connections. Looping of the service lines is recommended to minimize strain.
5. DO NOT use Vaseline®, plumber's grease, or any other petroleum based product on seals or o-rings.

Damage caused by improper use and/or handling will void our warranty

WARNING: It is unlawful in CALIFORNIA & VERMONT (effective 1/1/2010); MARYLAND (effective 1/1/2012); LOUISIANA (effective 1/1/2013) and the UNITED STATES OF AMERICA (effective 1/4/2014) to use any product in the installation or repair of any public water system or any plumbing in a facility or system that provides water for human consumption if the wetted surface area of the product has a weighted average lead content greater than 0.25%. This prohibition does not extend to service saddles used in California, Louisiana or under USA Public Law 111-380. **WARNING:** This product can expose you to chemicals including lead, which is known to the State of CALIFORNIA to cause cancer and birth defects or other reproductive harm. For more information go to: www.P65Warnings.ca.gov.

3210-666

(OVER)

800.292.2737 | sales@aymcdonald.com | aymcdonald.com

4/22



IMPORTANT NOTICE - READ CAREFULLY

Installation Instructions

Copper Tube Slip Joint Compression Connector

A.Y. McDonald waterworks products are designed for reliable service. Like all brass products, however, they can be damaged by improper handling and use.

CAUTIONS

1. Protect threads. Avoid loose fitting wrenches. Do not drop or impact.
2. Use extra care with high water pressures (over 100 PSIG) and pipe over 1". Consult factory if desired.
3. Inspect and test all joints, valves and fittings before backfilling.
4. Backfill carefully so as to avoid damage to the service line and connections. Looping of the service lines is recommended to minimize strain.
5. DO NOT use Vaseline®, plumber's grease, or any other petroleum based product on seals or o-rings.

Damage caused by improper use and/or handling will void our warranty

WARNING: It is unlawful in CALIFORNIA & VERMONT (effective 1/1/2010); MARYLAND (effective 1/1/2012); LOUISIANA (effective 1/1/2013) and the UNITED STATES OF AMERICA (effective 1/4/2014) to use any product in the installation or repair of any public water system or any plumbing in a facility or system that provides water for human consumption if the wetted surface area of the product has a weighted average lead content greater than 0.25%. This prohibition does not extend to service saddles used in California, Louisiana or under USA Public Law 111-380. **WARNING:** This product can expose you to chemicals including lead, which is known to the State of CALIFORNIA to cause cancer and birth defects or other reproductive harm. For more information go to: www.P65Warnings.ca.gov.

3210-666

(OVER)

800.292.2737 | sales@aymcdonald.com | aymcdonald.com

4/22



IMPORTANT NOTICE - READ CAREFULLY

Installation Instructions

Copper Tube Slip Joint Compression Connector

A.Y. McDonald waterworks products are designed for reliable service. Like all brass products, however, they can be damaged by improper handling and use.

CAUTIONS

1. Protect threads. Avoid loose fitting wrenches. Do not drop or impact.
2. Use extra care with high water pressures (over 100 PSIG) and pipe over 1". Consult factory if desired.
3. Inspect and test all joints, valves and fittings before backfilling.
4. Backfill carefully so as to avoid damage to the service line and connections. Looping of the service lines is recommended to minimize strain.
5. DO NOT use Vaseline®, plumber's grease, or any other petroleum based product on seals or o-rings.

Damage caused by improper use and/or handling will void our warranty

WARNING: It is unlawful in CALIFORNIA & VERMONT (effective 1/1/2010); MARYLAND (effective 1/1/2012); LOUISIANA (effective 1/1/2013) and the UNITED STATES OF AMERICA (effective 1/4/2014) to use any product in the installation or repair of any public water system or any plumbing in a facility or system that provides water for human consumption if the wetted surface area of the product has a weighted average lead content greater than 0.25%. This prohibition does not extend to service saddles used in California, Louisiana or under USA Public Law 111-380. **WARNING:** This product can expose you to chemicals including lead, which is known to the State of CALIFORNIA to cause cancer and birth defects or other reproductive harm. For more information go to: www.P65Warnings.ca.gov.

3210-666

(OVER)

800.292.2737 | sales@aymcdonald.com | aymcdonald.com

4/22