
## SUBMITTAL DATA SHEET

## NL Service Fitting – 74758-22-67



-22 CTS Compression x -67 XS Lead Compression



MODEL NO,	SIZE	A	В	С	D	E
74758-22-67	3/4	2.07	l.34	HEX	3⁄4	3⁄4
74758-22-67	3/4 X 1/2	2,00	l.34	OCT	3/4	1/2
74758-22-67	3/4 X 5/8	2.11	1.38	OCT	3⁄4	5⁄8
74758-22-67	3⁄4 X 1	2.44	l.85	OCT	3⁄4	1
74758-22-67	1	2.36	l.85	OCT	1	1
74758-22-67	1 X 5⁄8	2,40	l.38	OCT	1	5⁄8
74758-22-67	1 X 3⁄4	Э,04	l.78	HEX	1	3/4
74758-22-67	1 X 1 1/4	2.60	2.06	OCT	1	1 1/4
74758-22-67	1 1/4 × 1	2.62	l.68	OCT	1 1/4	1
74758-22-67	1 1/2	2.62	2.44	OCT	1 1/2	1 1/2
74758-22-67	1 1/2 X 1 1/4	2.80	2,28	OCT	1 1/2	l 1/4
74758-22-67	2	2.89	3.13	OCT	2	2

## SUBMITTAL INFORMATION

- Manufactured in compliance with ANSI/AWWA C800 (latest revision)
- Brass components in contact with potable water conform to ASTM B584, UNS C89833 (latest revision) and identified with "NL"
- Certified to NSF/ANSI 61 and NSF/ANSI 372
- Brass components not in contact with potable water conform to ASTM B62 and ASTM B584, UNS C83600 -85-5-5-5 (latest revision)
- Large wrench flats provided for proper installation
- Insert stiffeners required on all flexible plastic connections



**A.Y. McDonald Mfg. Co.** 4800 Chavenelle Rd Dubuque, IA 52002 **Toll Free:** 1-800-292-2737 sales@aymcdonald.com <u>aymcdonald.com</u>

A.Y. McDonald considers the information on this assembly drawing correct when published. Item and option availability, including specifications, are subject to change without notice.

## Submitted by: