
# SUBMITTAL DATA SHEET

Dewatering Pumps
Electric & DC Powered | Engine Driven


## Mini Mac - Transfer Pump Kits




### **Application:**

Emptying water heaters, bilge pumping, bait tanks, liquid transfer, clogged sinks, dewatering, and any common small household job.
\*Medium being pumped must be compatible witah pump materials. Not for use with flammable liquids.

# **300611TPK Dimensions | 115V AC** 3/4" Garden Hose Threads External







Model Includes:


Replacement impeller



Puddle scoop and 6' suction hose for draining flat surfaces







### Performance (GPH)

Model									
300611TPK	400	390	358	330	295	225	120	48	6

Part No.	Model	Description	Wt.
6195-010	300622RK	Impeller Repair Kit	1
(Use repair parts discount)			

### Specifications -

Power supply required	115V 60 Hz
Motor, full load amps (fuse size)	2.0 Amps
Motor type (design)	Universal
Motor leads and length	6' Cord
HP	1/6
Dimensions (overall) not include base	6 1/4" L x 3 1/2" H x 3 1/4" W
Maximum liquid temperature	130°F
Minimum	40°F
Pump body material	Environmental Safe, No-Lead Alloy

Impeller & lip seal	Nitrile
Lip seal metal retain	BL 22
Motor shaft material	416 S.S.
Ports	3/4" external hose, Thread suction & discharge
Pump gasket	Paper
Cover	316 S.S.
Screws	18-8 S.S.
Slinger	Neoprene
Shipping weight	6 lbs.

### SUBMITTAL INFORMATION

- Buna N impeller and lip seal
- Inlet and outlet are 3/4" male garden hose

- Self priming to 7 feet
- Available 115V AC

NO-LEAD: The weighted average of the wetted surface of this no-lead product contacted by consumable water contains less than one quarter of one percent (0.25%) lead.



**A.Y. McDonald Mfg. Co.** 4800 Chavenelle Rd Dubuque, IA 52002

**Toll Free:** 1-800-292-2737 sales@aymcdonald.com aymcdonald.com

A.Y. McDonald considers the information on this assembly drawing correct when published. Item and option availability, including specifications, are subject to change without notice.

Submitted by: