
SUBMITTAL DATA SHEET

 $\begin{array}{c} \text{Stainless-Steel Threaded Fitting} \\ \text{Cap}-2201\text{SS} \end{array}$



A.Y. M^cDonald Mfg. Co. Pipe Fittings are constructed from 304 stainless-steel and are rated for commerical, industrial and residential applications up to 150 PSI. Threads conform to MSS-SP114 standards and specifications.



Part No.	Model No.	Size	Dimensions A	Dimensions B	Dimensions C	Carton Qty	Weight Per Pcs.
4428-060	2201SS	1/8"	.75	.25	.68	150	.04
4428-061	2201SS	1/4"	.84	.32	.68	100	.05
4428-062	2201SS	3/8"	1.01	.36	.81	80	.07
4428-063	2201SS	1/2"	1.20	.43	.93	60	.14
4428-064	2201SS	3/4"	1.46	.50	1.06	30	.21
4428-065	2201SS	1"	1.77	.58	1.31	15	.37
4428-066	2201SS	1 1/4"	2.15	.67	1.62	8	.62
4428-067	2201SS	1 1/2"	2.43	.70	1.62	30	.79
4428-068	2201SS	2"	2.96	.75	1.75	5	1.20

SUBMITTAL INFORMATION

- Rated

150 PSI max pressure

Material

_

- 304 Stainless-Steel
- Fitting Dimensions
- MSS SP-114

NO-LEAD: The weighted average of the wetted surface of this no-lead product contacted by consumable water contains less than one quarter of one percent (0.25%) lead.



A.Y. McDonald Mfg. Co. 4800 Chavenelle Rd Dubuque, IA 52002 **Toll Free:** 1-800-292-2737 sales@aymcdonald.com aymcdonald.com

A.Y. McDonald considers the information on this assembly drawing correct when published. Item and option availability, including specifications, are subject to change without notice.

Submitted by: